


## **CUSTOMER DATASHEET**


Printed: 08/11/2023


Product Management
Transportation Europe

Central Article Code: LH4085C16-B Created: 24/02/2020

Local Code: EA1050 Modified: 23/02/2021







Final Outlook LH416-B
Approval date 01/02/2021

#### **PERFORMANCES**

Voltage (V): 12 V

C20 (Ah): 105.0 20 h Cranking (A): 850 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

## STD. DIMENSIONS

Length (mm ± 2): 315

Width (mm  $\pm$  2): 175 Height (mm  $\pm$  2): 205 Total Weight (kg  $\pm$  5%): 23.10

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

# CONTAINER

Type: LH4 BLACK Hold Down: B13

Hold Down: B13 H.D. Adapter: No

#### COVER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters

Lateral Plug: Standard Left side BLACK

shape

#### **PLUGS**

Type: 1 x Vent Sealed PSL-OE ha BLACK

### **HANDLES**

Type: 2 x PSL OE Integrated BLACK

#### **OTHERS**

Degassing Tube: No

C.O. from LH4085C01-C (PSL-AM to PSL-OE)