| TECHNOLOGIES | CU | STOMER D | DATASHEE | Т | Printed: 08/11/2023 Product Management Transportation Europe |
|--|---|--|---|---|--|
| Central Article Code: | C76008A0 | 3-A | | Created: | 16/06/2011 |
| Local Code: | EK143 | | | Modified: | 14/03/2019 |
| | | (95) | | | |
| | (15 | | 13.5±1) Final Out S S V | | |
| | | | | | |
| PER | FORMANCES | 5 | | CONTAINE | R |
| | FORMANCES | 6 | Туре: | CONTAINE C76 | BLACK |
| Voltage (V): | | 20 h | Type: Hold Down: | | |
| /oltage (V): C20 (Ah): | 12 V | | | C76 | |
| /oltage (V): C20 (Ah): Cranking (A): | 12 V 14.0 | 20 h | Hold Down: | C76 B0 No | |
| /oltage (V): C20 (Ah): Cranking (A): Charge: | 12 V 14.0 80 CHARGED | 20 h | Hold Down: H.D. Adapter: | C76 B0 No COVER | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: | 12 V 14.0 80 CHARGED AGM | 20 h | Hold Down: H.D. Adapter: Type: | C76 B0 No COVER Flat/Screw | |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: | 12 V 14.0 80 CHARGED AGM Ca/Ca | 20 h Not applicable | Hold Down: H.D. Adapter: | C76 B0 No COVER | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 | 20 h Not applicable ?Hz/6g/20h) | Hold Down: H.D. Adapter: Type: Polarity: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: | 12 V 14.0 80 CHARGED AGM Ca/Ca | 20 h Not applicable ?Hz/6g/20h) | Hold Down: H.D. Adapter: Type: Polarity: Terminals: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No | BLACK |
| /oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: STD. | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent | BLACK |
| /oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No No | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No PLUGS | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 6 x Valve+ | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No No | BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 6 x Valve- | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No PLUGS +Cover | BLACK BLACK BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 6 x Valves | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No PLUGS +Cover HANDLES | BLACK BLACK BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): Total Weight (kg ± 5%): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 4.20 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 6 x Valve+ | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No PLUGS +Cover | BLACK BLACK BLACK |
| Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2): | 12 V 14.0 80 CHARGED AGM Ca/Ca V3 (30Hz+/-2 300 cycles@ DIMENSIONS 150 100 100 4.20 | 20 h Not applicable 2Hz/6g/20h) 75% | Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 6 x Valves | C76 B0 No COVER Flat/Screw ETN 3 Screwed/Lug No No Independent No No PLUGS +Cover HANDLES | BLACK BLACK BLACK |

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.