


CUSTOMER DATASHEET


Printed: 08/11/2023


Product Management Transportation Europe

L04084A14-D Created: 31/01/2022 Central Article Code:

Modified: 21/09/2022 Local Code: EK820







Final Outlook L0414-D Approval date 15/10/2013

P	F	R	F	O	R	M	Δ	N	C	F	S
	_			u	•	IVI	_		v	_	•

Voltage (V): 12 V

C20 (Ah): 82.0 20 h 800 ΕN Cranking (A):

CHARGED Charge:

Technology: **AGM** Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: E4 EN50342-6

L04

BLACK Type: B13 Hold Down:

H.D. Adapter: No

COVER

CONTAINER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

2 Filters Filter:

Lateral Plug: Standard Right side BLACK

shape

PLUGS

Type: 1 x Vent Sealed (Valve) **BLACK**

HANDLES

BLACK 2 x Integrated Type:

OTHERS

Degassing Tube: No

STD. DIMENSIONS

Length (mm ± 2): 315

Width (mm ± 2): 175 Height (mm ± 2): 190 Total Weight (kg ± 5%): 23.30

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.