


# **CUSTOMER DATASHEET**


Printed: 09/11/2023


Product Management
Transportation Europe

Central Article Code: L03068C14-B Created: 22/09/2005

Local Code: EN750 Modified: 10/01/2023







inal Outlook	L0314-B
Approval date	01/04/2008

**CONTAINER** 

PERFORMANCES				
Voltage (V):	12 V			
C20 (Ah):	74.0	20 h		
Cranking (A):	680	EN		
Charge:	WET			
Technology:	Vented/FI	Vented/Flooded		
Grid:	Ca/Ca	Ca/Ca		
Vibration:	V1 (30Hz-	V1 (30Hz+/-2Hz/3g/2h)		
Endurance:	E1 (180 c	E1 (180 cycles@25%)		

STD. DIMENSIONS				
Length (mm ± 2):	278			

Width (mm ± 2):	175
Height (mm ± 2):	190
Total Weight (kg ± 5%):	16.60

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type:	L03	BLACK
	5.40	

Hold Down: B13 H.D. Adapter: No

## COVER

Type: NPR BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters

Lateral Plug: Standard Right side BLACK

shape

### **PLUGS**

Type: 1 x NPR (Manifold) BLACK

## **HANDLES**

Type: 1 x NPR (Thin) BLACK

#### **OTHERS**

Degassing Tube: No