


CUSTOMER DATASHEET


Printed: 09/11/2023


Product Management
Transportation Europe

Central Article Code: M08130S01-A Created: 07/09/2005

Local Code: EU260-6 Modified: 04/03/2014







Final Outlook M0801-A Approval date 01/05/2011

PERFORMANCES

Voltage (V): 6 V

C20 (Ah): 260.0 20 h Cranking (A): 1300 EN

Charge: WET

Technology: Vented/Flooded

Grid: Low Sb

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: E2 (90 cycles@50%)

CONTAINER

Type: M08 BLACK

Hold Down: B0 H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 345

 Width (mm \pm 2):
 172

 Height (mm \pm 2):
 286

 Total Weight (kg \pm 5%):
 39.10

PLUGS

Type: 3 x M27(STE) GREY MEDIUM

HANDLES

Type: 2 x Rigid BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.